Mine Safety Appliances Company
Cranberry Township, Pennsylvania, USA
1-800-672-2222

Advantage GMA Cartridge 815141

This cartridge is approved only in the following configurations:

RESPIRATOR COMPONENTS

TC-	PROTECTION[1]	ALTERNATE FACEPIECE																																		INLET ASSY	APR. ADAPTER			ADAPTER ASSY	FACEPIECE ADAPTER				CARTRIDGE	ALTERNATE NOSECUPS									ALTERNATE HOSE				BREATHING TUBE		ALT. VALVE ASSY.		ALTERNATE BELTS				CAUTIONS AND LIMITATIONS[2]
		ADVANTAGE 3200 SM/ MED/ LG	ADVANTAGE 200 LS MEDIUM	ADVANTAGE 200 LS SMALL	ADVANTAGE 200 LS LARGE	ADVANTAGE 1000 MEDIUM	ADVANTAGE 1000 SMALL	ADVANTAGE 1000 LARGE	ULTRAVUE, MED	ULTRAVUE, SMALL	ULTRAVUE, LARGE	ULTRAVUE, MED	ULTRAVUE, SMALL	ULTRAVUE, LARGE	ULTRAVUE, MED	ULTRAVUE, SMALL	ULTRAVUE, LARGE	ULTRAVUE, SMALL	ULTRAVUE, SMALL, NFPA	ULTRAVUE, MED	ULTRAVUE, MED, NFPA	ULTRAVUE, LARGE	ULTRAVUE, LARGE, NFPA	ULTRA ELITE, SMALL	ULTRA ELITE, SMALL, NFPA	ULTRA ELITE, MED,	ULTRA ELITE, MED., NFPA	ULTRA ELITE, LARGE	ULTRA ELITE, LARGE NFPA	ADVANTAGE 4100 SERIES SM / MED / LRG HYCAR	ADVANTAGE 4100 SERIES SM / MED / LRG SILICONE	ADVANTAGE 4200 SERIES SM / MED / LRG HYCAR	ADVANTAGE 4200 SERIES SM / MED / LRG SILICONE	ADVANTAGE 420 MEDIUM	ADVANTAGE 420 SMALL	ADVANTAGE 420 LARGE	INLET ASSEMBLY, Rd 40 THREAD, DEMAND, ADVANTAGE 4000	APR ADAPTER	APR ADAPTER - SLIDE TYPE	APR ADAPTER - PUSH TO CONNECT TYPE	ADAPTER ASSY	ADAPTER ASSY., ULTRA ELITE MMR 1/4 TURN QK. DIS.	ADAPTER ASSY., SLIDE TYPE FIREHAWK	ADAPTER, PUSH TO CONNECT	ADAPTER, PLUGGED, ADVANTAGE 4000	ADAPTER, TWIN CARTRIDGE, ADVANTAGE 4000	GMA ADVANTAGE	ADVANTAGE 1000 MEDIUM	ADVANTAGE 1000 MEDIUM	ADVANTAGE 1000 SMALL	ADVANTAGE 1000 SMALL	ADVANTAGE 1000 LARGE	ADVANTAGE 1000 LARGE	ULTRAVUE, SMALL	ULTRAVUE, MED	ULTRAVUE, LARGE	ULTRAVUE	AIR HOSE ASSY. 375"I.D. PVC, STRAIGHT	AIR HOSE ASSY. 375"I.D. PVC, STRAIGHT, 100 FT	AIR HOSE ASSY. 375"I.D. NEOPRENE, STRAIGHT,	AIR HOSE ASSY 3/8" I.D. COILED	BREATHING TUBE ASSEMBLY	BREATHING TUBE ASSEMBLY	VALVE, ADJUSTABLE AIRLINE, FLOW CONTROL HP	VALVE, NON-ADJUSTABLE AIRLINE, FLOW CONTROL HP	Belt Assembly	Belt Assembly	Belt Assembly	Belt Assembly	
		3200	7-1609-1	7-1609-2	7-1609-3	7-1293-1	7-1293-2	7-1293-3	7-212-1	7-212-2	7-212-3	7-212-4	7-212-5	7-212-6	7-948-1	7-948-2	7-948-3	7-948-5	7-948-8	7-948-4	7-948-7	7-948-6	7-948-9	7-935-2	7-935-5	7-935-1	7-935-4	7-935-3	7-935-6	4100-H	4100-S	4200-H	4200-S	10092349	10092348	10092350	10066330	10029823	10032511	10040052	96547	813556	10018621	10033115	10066332	10066328	815141	805125	805126	805127	805128	805129	805130	471539	471540	471541	96671	7-864-1	7-864-2	7-865-1	5-511-1	457158	456651	5-713-1	5-622-1	7-977-1	9961	473902	487446	
23C-2140	OV								X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X								X	X	X		X	X	X	X		X									X	X	X	X													ABCHIJLMNO
23C-2314	OV																													X	X	X	X												X	X	X																							ABCHIJLMNO
23C-2331	OV/CF/SA																															X	X				X					X						X											X	X	X	X	X	X	X	X	X	X	X	X	ABCHIJLMNO
23C-2678	OV		X	X	X																																										X																						ABCHIJLMNO
23C-2670	OV					X	X	X																																							X	X	X	X	X	X	X															ABCHIJLMNO
23C-2686	OV	X																																													X																						ABCHIJLMNO
23C-2693	OV																																	X	X	X											X																							ABCHIJLMNO

1. PROTECTION

OV - Organic Vapors

CF- CONTINUOUS-FLOW

SA - SUPPLIED AIR

2. CAUTIONS AND LIMITATIONS

A- Not for use in atmospheres containing less than 19.5 percent oxygen.

B- Not for use in atmospheres immediately dangerous to life or health.

C- Do not exceed maximum use concentrations established by regulatory standards.

H- Follow established cartridge and canister change schedules or observe ESLI to ensure that cartridges and canisters are replaced before breakthrough occurs.

I- Contains electrical parts that may cause an ignition in flammable or explosive atmospheres.

J- Failure to properly use and maintain this product could result in injury or death.

L- Follow the manufacturer's User's Instructions for changing cartridges and / or filters

M- All approved respirators shall be selected, fitted, used, and maintained in accordance with MSHA, OSHA, and other applicable regulations.

N- Never substitute, modify, add, or omit parts. Use only exact replacement parts in the configurations as specified by the manufacturer.

O- Refer to User's Instructions, and / or maintenance manuals for information on use and maintenance of these respirators.

CONTROL BOX
Mat. 10035540
Doc. 10000012708
REV 7 5/13/11
ADVANTAGE 200 GMA CART.
Prmt Spec. 10000005412
F
TAL 6-3-11