

# NIGHTSTICK<sup>®</sup>

Life Depends on Light™

## Intrinsically Safe Permissible Polymer Penlight

This non-rechargeable penlights is cETLus, ATEX, IECEx and MSHA listed Intrinsically Safe Permissible . It is ultra-compact and super slim with a powerful light output designed to illuminate very tight spaces. The tail-cap switch provides momentary or constant-on functionality. Power comes from 2 AAA premium batteries (included).

**INTRINSICALLY SAFE  
PERMISSIBLE**



**30** Lumens

- cETLus, ATEX, IECEx and MSHA listed Intrinsically Safe Permissible
- Engineered polymer housing
- Powered by AAA batteries



**XPP 5410G**



High-efficiency deep parabolic reflector

## Intrinsically Safe Permissible Polymer Penlight




XPP-5410G

### FEATURES

- CREE® LED technology – 50,000 + hours LED life
- Momentary or constant-on flashlight
- Sharp focused beam for distance illumination
- Engineered polymer housing
- Single tail switch
- Waterproof
- Impact & chemical resistant
- Built-in pocket/belt clip
- Powered by 2 AAA batteries (included)
- Limited Lifetime Warranty\*

### XPP-5410G SPECIFICATIONS

- Lumens: 30
- Run-time: 18 hrs
- Beam distance: 40 meters
- Water rating: IP-X7 waterproof
- Drop rating: 2 meters
- Length: 5.8in, head diameter: 0.9in, handle diameter: 0.7in, weight: 1.9oz



### INCLUDED

- Flashlight
- 2 AAA premium alkaline batteries

### SAFETY RATING

cETLus, ATEX, IECEx and MSHA listed Intrinsically Safe Permissible.

Patent 7,738,229

Model	UPC 0 17398
XPP-5410G	80298 7



Handheld

High-efficiency deep parabolic reflector

Push-button tail-cap switch

Permissible XPP-5410 Flashlight Assembly

**MSHA** APPROVAL No. 20-A140006-0

TESTED FOR INTRINSIC SAFETY IN METHANE-AIR MIXTURES ONLY

WARNINGS: The Model XPP-5410 is MSHA approved for use with Energizer (Type E92), two Energizer (Type EN92), and Duracell (Type MX2400), Duracell (PC2400), and Duracell (EN92) batteries only. Replace the batteries in fresh air only and replace all batteries at the same time. Do not mix batteries from different manufacturers or of different types. The Model XPP-5410 must not be opened in area where permissibility required.

 Intertek ID 4001184 INTRINSICALLY SAFE SECURITE INTRINSEQUE	CLASS I DIV 1 GRPS A-D T3 CLASS II & III DIV 1 GRPS E-G T135C CLASS I ZONE 0 AEx ia IIC T3 Ga CLASS I ZONE 0 Ex ia IIC T3 Ga Ⓢ IM 1 Ex ia op is I Ma Ⓢ IM 1 G Ex ia op is IIC T3 Ga	Ex ia op is I Ma Ex ia op is IIC T3 Ga Intertek ITS 13 ATEX27839X IECEx TS 14.0036X -20°C ≤ Tamb ≤ +40°C 1.5V/Cell AAA Alkaline
	CE 0359	

<b>Conforms to:</b> ANSI/UL STD 913, ANSI/UL 60079-0, ANSI/UL 60079-11 ANSI/ISA 60079-26	<b>Certified to:</b> CAN/CSA STD C22.2 No 157 CAN/CSA STD C22.2 No 60079-0 CAN/CSA STD C22.2 No 60079-11 CSA STD C22.2 No 25
---	--

\*Limited Lifetime Warranty • Product is warranted to be free from defects in workmanship and materials for the original purchaser's lifetime. The Limited Lifetime Warranty includes the LEDs, housing and lenses. Rechargeable batteries, chargers, switches, electronics and included accessories are warranted for a period of two (2) years with proof of purchase. Disposable, non-rechargeable batteries are excluded from this warranty. Normal wear and failures which are caused by accidents, misuse, abuse, faulty installation and lightning damage are also excluded.