



Intrinsically Safe Permissible Polymer Flashlights

These non-rechargeable flashlights are cETLus, ATEX, IECEx and MSHA listed Intrinsically Safe Permissible. They each use a CREE® LED rated at 140 lumens that works in conjunction with a high-efficiency deep parabolic reflector to create a usable flashlight beam rated at 180 meters. The single body switch provides momentary or constant-on functionality. Power comes from 3 AA premium batteries (not included).

**INTRINSICALLY SAFE
PERMISSIBLE**



XPP-5420G

140 Lumens

- cETLus, ATEX, IECEx and MSHA listed Intrinsically Safe Permissible
- Beam distance rated at 180 meters
- Engineered polymer housing



XPP-5420B

XPP 5420 series



XPP 5420 series



Intrinsically Safe Permissible Polymer Flashlights

High-efficiency deep parabolic reflector



XPP-5420G



XPP-5420B

FEATURES

- CREE® LED technology – 50,000 + hours LED life
- Momentary or constant-on flashlight
- Sharp focused beam for distance illumination
- Engineered polymer housing
- Non-slip grip
- Single body switch
- Waterproof
- Impact & chemical resistant
- Built-in pocket/belt clip
- Includes removable lanyard
- Requires 3 AA batteries (not included)
- Available in black & green
- Limited Lifetime Warranty*



Built in pocket/belt clip




Single body switch



High-efficiency deep parabolic reflector

SPECIFICATIONS

- Lumens: 140
- Run-time: 14 hrs
- Beam distance: 180 meters
- Water rating: IP-X7 waterproof
- Drop rating: 2 meters
- Length: 7in, head diameter: 1.8in, handle diameter: 1.5 x 1.1in, weight: 7.3oz



INCLUDED

- Flashlight with built-in pocket/belt clip
- Removable lanyard

SAFETY RATING

cETLus, ATEX, IECEx and MSHA listed Intrinsically Safe Permissible

Patent 7,738,229



Permissible Nightstick 5420 Flashlight/Floodlight
APPROVAL No. 20-A130001-0

TESTED FOR INTRINSIC SAFETY IN METHANE-AIR MIXTURES ONLY

WARNINGS: 1) MSHA approved for use with three AA Duracell Type PC1500, Energizer Type EN91, and Energizer Type L91 batteries only.
2) Replace the batteries in fresh air only and replace all batteries at the same time. Do not mix batteries from different manufacturers or of different types.
3) Energizer Lithium (Type L91) batteries are to be replaced by a qualified technician only.
4) The Model Nightstick 5420 must not be opened in areas where permissibility is required.

CLASS I DIV 1 GRPS A-D T3 Ex ia I Ma
CLASS II & III DIV 1 GRPS E-G T135C Ex ia IIC T3 Ga
CLASS I ZONE 0 AEx ia IIC T3 Ga Intertek ITS 13 ATEX27837X
CLASS I ZONE 0 Ex ia IIC T3 Ga IECEx ETL 13 0026X
-20°C ≤ Tamb ≤ +40°C
1.5V/Cell AA Alkaline

ID 4003544
INTRINSICALLY SAFE
SECURITE INTRINSEQUE

CE 0359

Conforms to:
ANSI/UL STD 913, ANSI/UL 60079-0, ANSI/UL 60079-11, ANSI/ISA 60079-26

Certified to:
CAN/CSA STD C22.2 No 157, CAN/CSA STD C22.2 No 60079-0, CAN/CSA STD C22.2 No 60079-11, CSA STD C22.2 No 25

Model	UPC 0 17398
XPP-5420G	80091 4
XPP-5420B	80092 1

*Limited Lifetime Warranty • Product is warranted to be free from defects in workmanship and materials for the original purchaser's lifetime. The Limited Lifetime Warranty includes the LEDs, housing and lenses. Rechargeable batteries, chargers, switches, electronics and included accessories are warranted for a period of two (2) years with proof of purchase. Disposable, non-rechargeable batteries are excluded from this warranty. Normal wear and failures which are caused by accidents, misuse, abuse, faulty installation and lightning damage are also excluded.