

XPP-5422GM

Intrinsically Safe Permissible Dual-Light™ Flashlight w/ Dual Magnets

MARKET APPLICATIONS	Hazardous work environments, industrial, automotive, law enforcement, fire & rescue
DESCRIPTION	This non-rechargeable Dual-Light™ Flashlight is cETLus, ATEX, IECEx and MSHA listed Intrinsically Safe Permissible. It uses as CREE® LED rated at 120 lumens that works in conjunction with a high-efficiency deep parabolic reflector to create a usable flashlight beam rated at 170 meters. A 120 lumens unfocused floodlight is integrated into the housing which is perfect for close-up illumination. Additionally both the flashlight and the floodlight can be turned on at the same time for maximum versatility. The dual body switches provide momentary or constant-on functionality for the flashlight and on/off functionality for the floodlight. Additionally, the integrated magnets located in the base of the handle and the pocket clip, provide for almost limitless hands-free usage. Power comes from 3 AA premium batteries (not included).
CASE MATERIAL	Engineered Polymer - Green
DIMENSIONS	Length: 7.2 inches (183 mm) • Head Diameter: 1.8 inches (46 mm) • Handle Diameter: 1.1 x 1.5 inches (28 x 38 mm)
WEIGHT	Weight: 6.9 oz. (196 g) with batteries installed
LENS	Unbreakable polycarbonate with scratch resistant coating
LIGHT SOURCE	Flashlight: CREE® LED Impervious to shock with a 50,000 hour lifetime
LIGHT OUTPUT	Flashlight: 120 lumens, Floodlight: 120 lumens, Dual-Light: 240 lumens
ON/OFF	Dual Body Switch - Momentary or Constant-on Flashlight, Constant-on Floodlight
RUN-TIME	Flashlight: 17.5 hours, Floodlight: 17.5 hours, Dual-Light: 4.5 hours
BATTERY	3 Alkaline AA batteries (not included)
FEATURES	<ul style="list-style-type: none"> • cETLus, ATEX, IECEx and MSHA listed Intrinsically Safe Permissible • Flashlight – Floodlight – Dual-Light™ • CREE® LED technology – 50,000 + hours LED life • Momentary or constant-on flashlight • Sharp focused flashlight beam for distance illumination • Unfocused wide-beam floodlight for close-up illumination • Dual-light (flashlight & floodlight at same time) for maximum versatility • Powerful integrated magnets built into the base and pocket clip for multiple hands-free options • Engineered polymer housing w/ Non-slip grip • Dual body switches • Waterproof • Impact & chemical resistant • Built-in pocket/belt clip • Includes removable lanyard • Requires 3 AA batteries

Permissible Nightstick 5422 Flashlight/Floodlight

MSHA APPROVAL No. 20-A130001-0

TESTED FOR INTRINSIC SAFETY IN METHANE-AIR MIXTURES ONLY

WARNINGS: MSHA approved for use with three AA Duracell Type PC1500, Energizer Type EN91, and Energizer Type L91 batteries only. Replace the batteries in fresh air only and replace all batteries at the same time. Do not mix batteries from different manufacturers or of different types. Energizer Lithium (Type L91) batteries are to be replaced by a qualified technician only. The Model Nightstick 5422 must not be opened in areas where permissibility is required.

 Intertek ID 4002026 INTRINSICALLY SAFE SECURITE INTRINSEQUE	CLASS I DIV 1 GRPS A-D T3 CLASS II & III DIV 1 GRPS E-G T135C CLASS I ZONE 0 AEx ia IIC T3 Ga CLASS I ZONE 0 Ex ia IIC T3 Ga © I M 1 Ex ia I Ma © II 1 G Ex ia IIC T3 Ga	Ex ia I Ma Ex ia IIC T3 Ga Intertek ITS 13 ATEX27837X IECEx ETL 13.0026X -20°C ≤ Tamb ≤ +40°C 1.5V/Cell AA Alkaline
---	---	--

CE 0359

Conforms to: ANSI/UL STD 913, ANSI/UL 60079-0, ANSI/UL 60079-11 ANSI/ISA 60079-26	Certified to: CAN/CSA STD C22.2 No 157 CAN/CSA STD C22.2 No 60079-0 CAN/CSA STD C22.2 No 60079-11 CSA STD C22.2 No 25
---	--

WARRANTY Limited Lifetime Warranty • Includes the LEDs, housing and lenses. Rechargeable batteries, chargers, switches, electronics and included accessories are warranted for a period of two years with proof of purchase. Disposable, non-rechargeable batteries are excluded from this warranty. Normal wear and failures which are caused by accidents, misuse, abuse, faulty installation and lightning damage are also excluded.

