

Rope grab Easy Move with lifeline

Vertical lifeline kit



The Easy Move device with lifeline is used to provide temporary fall protection on ladders or when climbing. This system can also be used to provide a secondary lifeline for suspended positioning systems used by building/structure inspectors, window cleaners, and maintenance personnel.

The vertical lifeline kit consists of 15, 20, 25 or 30 m of 11 mm polyamide rope with sewn eyelets, Easy Move device and carrying bag.



Features & Benefits

Features	Benefits
All-in-one fall arrester	Rope adjuster and a guided type fall arrester
Light weight and compact	For comfortable use and easy carrying
Developed to grip on dirty or icy ropes	High performance in the harshest environments
Two operation modes	REST – position in ascender mode/ lanyard adjustment GO – position in fall arresting mode

Product Specifications

Material	
Lifeline	11 mm polyamide rope with breaking strain ≥ 22 kN
Easy Move device	Aluminium and steel
Technical	
Operating temperature range	-30°C and +40°C
Maximum personnel capacity	100 kg
Weight of Easy Move device	190 g
Minimum recommended clearance	3.5 m
Certification	
EU	EN 12841:2006 EN 353-2:2002 EN 358:1999



Ordering Information

Description	Part. No
Rope grab Easy Move, Kit including 15 m, 11 mm rope (without carabiner), in the bag	10164578
Rope grab Easy Move, Kit including 20 m, 11 mm rope (without carabiner), in the bag	10164579
Rope grab Easy Move, Kit including 25 m, 11 mm rope (without carabiner), in the bag	10164580
Rope grab Easy Move, Kit including 30 m, 11 mm rope (without carabiner), in the bag	10164611