

XPP-5450G

Intrinsically Safe Dual-Function Headlamp

MARKET APPLICATIONS

Hazardous work environments, industrial, automotive, law enforcement, fire & rescue

DESCRIPTION

This non-rechargeable dual-function headlamp is cETLus, ATEX and IECEx listed Intrinsically Safe. This headlamp features a multi-position tilt head design and includes an elastic head strap with a non-slip lining and a heavy-duty rubber head strap for use on a hard hat. The top mounted switch provides user selectable high or low brightness spotlight operation. Power comes from 3 AAA premium batteries (included).

CASE MATERIAL Engineered Polymer - Green

DIMENSIONS Length: 2.4 inches (61 mm) • Width: 1.9 inches (48 mm) • Depth: 1.8 inches (46 mm)

WEIGHT Weight: 3.5 oz. (99 g) with batteries installed

Unbreakable polycarbonate with scratch resistant coating LENS CREE® LED Impervious to shock with a 50,000 hour lifetime **LIGHT SOURCE**

LIGHT OUTPUT High-Brightness Spotlight: 60 lumens, Low-Brightness Spotlight: 40 lumens ON/OFF Single Body Switch. High-Brightness Spotlight, Low-Brightness Spotlight High-Brightness Spotlight: 13.5 hours, Low-Brightness Spotlight: 22.75 hours **RUN-TIME**

BATTERY 3 Alkaline AAA batteries (included)

· cETLus, ATEX and IECEx listed Intrinsically Safe **FEATURES**


- CREE® LED technology 50,000 + hours LED life · High-brightness spotlight, low-brightness spotlight
- Focused spotlight beam for distance illumination
- Engineered polymer housing
- Single switch located on top of light
- Adjustable ratchet tilt head
- Non-slip elastic head strap
- Heavy-duty rubber strap for hard hat applications
- Waterproof
- Impact & chemical resistant
- · Powered by 3 premium AAA alkaline batteries (included)

NA	RR	AN	ΤY	
	••••	••••		

Limited Lifetime Warranty • Includes the LEDs, housing and lenses. Rechargeable batteries, chargers, switches, electronics and included accessories are warranted for a period of two years with proof of purchase. Disposable, non-rechargeable batteries are excluded from this warranty. Normal wear and failures which are caused by accidents, misuse, abuse, faulty installation and lightning damage are also excluded.

APPROVALS





FL1 STANDARD	HIGH	LOW
314	60 LUMENS	40 LUMENS
0	13h 30min	22h 45min
	80m	65m
	1615cd	1076cd
2m		
1m		

Nightstick 5450 Headlamp



ID 4001184 INTRINSICALLY SAFE SECURITE INTRINSEQUE

CLASS I DIV 1 GRPS A-D T3 CLASS II & III GRPS E-G T135C CLASS I ZONE 0 AEx ia IIC T3 Ga IECEx ETL 13.0031X CLASS I ZONE 0 Ex ia IIC T3 Ga © II 1 G Ex ia IIC T3 Ga

Ex ia IIC T3 Ga Intertek ITS 13 ATEX27854X -20°C ≤ Tamb ≤ +40°C 1.5V/Cell AAA Alkaline

C€ 0359

Conforms to: ANSI/UL STD 913, ANSI/UL 60079-0, ANSI/UL 60079-11 ANSI/ISA 60079-26

Certified to:

CAN/CSA STD C22.2 No 157 CAN/CSA STD C22.2 No 60079-0 CAN/CSA STD C22.2 No 60079-11 CSA STD C22.2 No 25

Designed in USA, manufactured in China at a ISO-9001 certified Bayco facility.

PDS_XPP-5450G_150420_A