

XPP-5452G

Intrinsically Safe Dual-Function Headlamp

MARKET APPLICATIONS

Hazardous work environments, industrial, automotive, law enforcement, fire & rescue

DESCRIPTION

This non-rechargeable dual-function headlamp is cETLus, ATEX and IECEx listed Intrinsically Safe. This headlamp features a multi-position tilt head design and includes an elastic head strap with a non-slip lining and a heavy-duty rubber head strap for use on a hard hat. The top mounted switch provides user selectable high or low brightness spotlight operation. Power comes from 3 AAA premium batteries (included).

CASE MATERIAL Engineered Polymer - Green

DIMENSIONS Length: 2.4 inches (61 mm) • Width: 1.9 inches (48 mm) • Depth: 1.8 inches (46 mm)

WEIGHT Weight: 3.5 oz. (99 g) with batteries installed

LIGHT SOURCE

Unbreakable polycarbonate with scratch resistant coating

CREE® LED Impervious to shock with a 50,000 hour lifetime

LIGHT OUTPUTHigh-Brightness Spotlight: 115 lumens, Low-Brightness Spotlight: 65 lumensON/OFFSingle Body Switch. High-Brightness Spotlight, Low-Brightness SpotlightRUN-TIMEHigh-Brightness Spotlight: 4.5 hours, Low-Brightness Spotlight: 13 hours

BATTERY 3 Alkaline AAA batteries (included)

• cETLus, ATEX and IECEx listed Intrinsically Safe


- CREE® LED technology 50,000 + hours LED life
 High-brightness spotlight, low-brightness spotlight
- · Focused spotlight beam for distance illumination
- · Engineered polymer housing
- Single switch located on top of light
- Adjustable ratchet tilt head
- Non-slip elastic head strap
- · Heavy-duty rubber strap for hard hat applications
- Waterproof
- · Impact & chemical resistant
- Powered by 3 premium AAA alkaline batteries (included)

WARRANTY

Limited Lifetime Warranty • Includes the LEDs, housing and lenses. Rechargeable batteries, chargers, switches, electronics and included accessories are warranted for a period of two years with proof of purchase. Disposable, non-rechargeable batteries are excluded from this warranty. Normal wear and failures which are caused by accidents, misuse, abuse, faulty installation and lightning damage are also excluded.

APPROVALS





FL1 STANDARD	HIGH	LOW
314	115 LUMENS	65 LUMENS
0	4h 30min	13h
	92m	67m
	2152cd	1141cd
2m		
1m		

Nightstick 5452 Headlamp



ID 4001184 INTRINSICALLY SAFE SECURITE INTRINSEQUE

Certified to:

CLASS I DIV 1 GRPS A-D T3
CLASS II & III GRPS E-G T135C
CLASS I ZONE 0 AEx ia IIC T3 Ga
CLASS I ZONE 0 Ex ia IIC T3 Ga
© II 1 G Ex ia IIC T3 Ga

Ex ia IIC T3 Ga Intertek ITS 13 ATEX27854X IECEx ETL 13.0031X -20°C ≤ Tamb ≤ +40°C 1.5V/Cell AAA Alkaline

C € 0359

Conforms to: ANSI/UL STD 913, ANSI/UL 60079-0, ANSI/UL 60079-11 ANSI/ISA 60079-26

CAN/CSA STD C22.2 No 157 CAN/CSA STD C22.2 No 60079-0 CAN/CSA STD C22.2 No 60079-11 CSA STD C22.2 No 25

Designed in USA, manufactured in China at a ISO-9001 certified Bayco facility.

PDS_XPP-5452G_150420_A